



OVERALL

* = lbs. (N)

inch (mm)

MODEL NO.	LENGTH H	BUNDLE DIA.	TENSILE STRENGTH *	A ^{±.003}	B ^{±.003}	C	D	E	F	G	I
RTHM-140D	15.38 (391)	4.00 (102)	120 (533)	.063 (2.1)	.310 (7.9)	.375 (9.5)	.300 (7.6)	.500 (12.7)	14.28 (363)	1.00 (25.4)	.25 (6.4)
RTHM-210D	22.00 (559)	6.00 (152)	120 (533)	.063 (2.1)	.310 (7.9)	.375 (9.5)	.300 (7.6)	.500 (12.7)	21.00 (533)	1.00 (25.4)	.25 (6.4)
RTHM-280D	29.00 (737)	8.00 (203)	120 (533)	.063 (2.1)	.310 (7.9)	.375 (9.5)	.300 (7.6)	.500 (12.7)	28.00 (711)	1.00 (25.4)	.25 (6.4)

ALL-STATES

RTHM-SERIES
CABLE TIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(X) +/- (XXX) = +/-
(XX) +/- ANGLES +/-

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE GIVEN
IN INCHES AND THIRD ANGLE
PROJECTION.

1 06-16-08 SB DRAWING NO. WAS 10001-7

DRAWN BY
WJB

MATERIAL

SCALE NONE

R 06-28-99 WJB REDRAWN

DATE
6-28-99

NYLON 6/6

DRAWING NO. ①
10007-C DWG.
A
SIZE

REV DATE BY CHK

DESCRIPTION

ECN - R CUST SUP

CHK'D.