



* = lbs. (N)

①

inch (mm)

MODEL NO.	OVERALL LENGTH H	BUNDLE DIA.	TENSILE STRENGTH *	MILITARY STD. NO.	A ^{±.003}	B ^{±.003}	C	D	E	F	G
RTE-1400	15.00 (381)	4.00 (101.6)	250 (1110)	MS3367-19	.083 (2.10)	.500 (12.7)	.625 (15.9)	.400 (10.2)	.875 (22.2)	14.45 (367)	1.00 (25.4)
RTE-1900 ①	19.70 (500)	5.00 (127)	250 (1110)	MS3367-20	.083 (2.10)	.500 (12.7)	.625 (15.9)	.400 (10.2)	.875 (22.2)	18.25 (469)	1.00 (25.4)
RTE-2100	21.88 (556)	6.00 (152.4)	250 (1110)	MS3367-21	.083 (2.10)	.500 (12.7)	.625 (15.9)	.400 (10.2)	.875 (22.2)	21.33 (542)	1.00 (25.4)
RTE-2800	28.75 (730)	8.00 (203.2)	250 (1110)	MS3367-22	.083 (2.10)	.500 (12.7)	.625 (15.9)	.400 (10.2)	.875 (22.2)	28.20 (716)	1.00 (25.4)

CUSTOMER DRAWING RTE-SERIES.DWG

⊕ = ALL-STATES

RTE-SERIES
CABLE TIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(X) +/- (XXX) =/-
(XX) +/- ANGLES +/-

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE GIVEN
IN INCHES AND THIRD ANGLE
PROJECTION.

REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP
2	6-19-08	SB		DRAWING NO. WAS 10001-9				
1	08-01-02	SB		ADDED MIL SPEC & NO.s RTE-1900 & FIXED DRWG.			SB	
R	07-12-88	WJB		RELEASED			WJB	

DRAWN BY
WJB
DATE
07-12-88
CHK'D.

MATERIAL
NYLON 6/6

SCALE NONE
DRAWING NO. ②
10009-C

DWG.
A
SIZE