



* = lbs. (N)

inch (mm)

MODEL NO.	OVERALL LENGTH H	BUNDLE DIA.	TENSILE STRENGTH *	A ^{±.003}	B ^{±.003}	C	D	E	F	G
RTDL 675	7.79 (198)	1.75 (44.5)	50 (222)	.055 (1.4)	.187 (4.7)	.54 (13.7)	.190 (4.8)	.315 (8.0)	7.25 (184)	1.22 (30.9)
RTDL 1100	11.79 (299.5)	3.00 (76.2)	50 (222)	.055 (1.4)	.187 (4.7)	.54 (13.7)	.190 (4.8)	.315 (8.0)	11.25 (286)	1.22 (30.9)
RTDL 1400	14.79 (378)	4.00 (102)	50 (222)	.055 (1.4)	.187 (4.7)	.54 (13.7)	.190 (4.8)	.315 (8.0)	14.25 (362)	1.22 (30.9)

** NYLON 6/6 UV WEATHERABLE
CONT. USAGE TEMP. RANGE:
-40°C TO 85°C (-40°F TO 185°F)

ALL-STATES

RTDL SERIES DOUBLE LOOP
CABLE TIES

CUSTOMER DRAWING FILE RTM-SERIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(X) +/- (XXX) =/-
(XX) +/- ANGLES +/-

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE GIVEN
IN INCHES AND THIRD ANGLE
PROJECTION.

DRAWN BY
WJB
DATE
5-02-00
CHK'D.

MATERIAL
NYLON 6/6
NYLON 6/6 UV -
WEATHERABLE **
Hi-Mont #SB-786
Co-Polymer - Polypropylene

SCALE NONE

DRAWING NO. ①
10010-C

DWG.
A
SIZE

1 6-19-08 SB

DRAWING NO. WAS 10001-10 &
ADDED NYLON 6/6-UV
Hi-Mont #SB-786
Co-Polymer - Polypropylene

R 05-02-00 WJB

REDRAWN

WJB

REV DATE BY CHK

DESCRIPTION

ECN - R CUST SUP