



BEADED TIE PART NO.	MAXIMUM BUNDLE DIA.		LOOP TENSILE		A	B	C	D	E	F	G	
			1. NYLON 2. POLYPROPYLENE 3. POLYETHYLENE									
			LESS	Kg.								
BT-4	1.12	(29)	1	40	18.0	4.28 (109)	.095 (2.4)	.250 (6.3)	.060 (1.5)	.125 (3.1)	.62 (15.7)	.06 (1.52)
			2	27	12.0							
			3	10	4.5							
BT-5	1.38	(35)	1	40	18.0	5.08 (129)	.097 (2.4)	.250 (6.3)	.060 (1.5)	.132 (3.3)	.62 (15.7)	.06 (1.52)
			2	27	12.0							
			3	10	4.5							
BT-6	1.88	(47)	1	75	33.8	6.62 (168)	.121 (3.0)	.367 (9.3)	.078 (1.9)	.250 (6.3)	1.10 (28.0)	.10 (2.54)
			2	36	16.3							
			3	18	8.1							
BT-8	2.50	(64)	1	75	33.8	8.90 (226)	.121 (3.0)	.367 (9.3)	.078 (1.9)	.250 (6.3)	1.10 (28.0)	.10 (2.54)
			2	36	16.3							
			3	18	8.1							
BT-10	3.00	(76)	1	75	33.8	10.78 (274)	.121 (3.0)	.367 (9.3)	.078 (1.9)	.250 (6.3)	1.10 (28.0)	.10 (2.54)
			2	36	16.3							
			3	18	8.1							
BT-14	4.00	(102)	1	75	33.8	15.22 (387)	.121 (3.0)	.367 (9.3)	.078 (1.9)	.250 (6.3)	1.10 (28.0)	.10 (2.54)
			2	36	16.3							
			3	18	8.1							
BT-17	5.00	(127)	1	75	33.8	18.22 (463)	.121 (3.0)	.367 (9.3)	.078 (1.9)	.250 (6.3)	1.10 (28.0)	.10 (2.54)
			2	36	16.3							
			3	18	8.1							

INCHES (MM)

ALL-STATES

RTBT SERIES BEADED TIES  
CABLE TIES

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONAL TOLERANCES ARE:  
(X) +/- (XXX) +/-  
(XX) +/- ANGLES +/-

UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE GIVEN  
IN INCHES AND THIRD ANGLE  
PROJECTION.

DRAWN BY  
WJB  
DATE  
5-3-00  
CHK'D.

MATERIAL

SEE CHART ABOVE

SCALE

NONE

DRAWING NO.

10011-C

DWG.

A  
SIZE

1 6-20-08 SB DRAWING NO. WAS 10001-11

REV DATE BY CHK DESCRIPTION

ECN - R CUST SUP