



MODEL NO.	OVERALL LENGTH $L \pm .08$	BUNDLE DIA.	TENSILE STRENGTH	MILITARY STD. NO.	A	$B \pm .08$
RTID-675	7.50 (191)	3/8 - 1 3/4	50 lbs (222)	MS3368-1	.035 (0.9)	1.18 (30.0)
RTID-1100	11.50 (292)	3/4 - 3	50 lbs (222)	NONE	.045 (1.1)	2.25 (57.2)
RTID-1400	14.50 (368)	3/4 - 4	50 lbs (222)	MS3368-2	.045 (1.1)	2.25 (57.2)

CUSTOMER DRAWING

AS ALL-STATES INC.
1801 W. Foster Ave. Chicago, IL 60640

RTID-SERIES CABLE TIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(X) +/- (XXX) +/- .005
(XX) +/- ANGLES +/-

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE GIVEN
IN INCHES AND THIRD ANGLE
PROJECTION.

DRAWN BY MATERIAL

SCALE NONE

DATE

NATURAL
NYLON 6/6

DRAWING NO.

10013-C

DWG.

A
SIZE

1 3-13-08 S.B. S.B. REDRAWN

REV DATE BY CHK DESCRIPTION ECN - R CUST SUP