


BEADED TIE PART NO.	MAXIMUM BUNDLE DIA.		LOOP TENSILE		A	B	C	D	E	F	G	H	I	
	INCHES	(MM)	1. NYLON 2. POLYPROPYLENE 3. POLYETHYLENE											
			LBS.	Kg.										
BTID-10	3.00	(76)	1	75	33.8	11.75 (298.5)	.121 (3.0)	.078 (1.9)	.250 (6.3)	.48 (12.2)	.10 (2.54)	1.00 (25.4)	.50 (12.7)	.85 (21.6)
			2	36	16.3									
			3	18	8.1									
BTID-14	4.00	(102)	1	75	33.8	15.75 (400.1)	.121 (3.0)	.078 (1.9)	.250 (6.3)	.48 (12.2)	.10 (2.54)	1.00 (25.4)	.50 (12.7)	.85 (21.6)
			2	36	16.3									
			3	18	8.1									
BTID-17	5.00	(127)	1	75	33.8	18.75 (476.3)	.121 (3.0)	.078 (1.9)	.250 (6.3)	.48 (12.2)	.10 (2.54)	1.00 (25.4)	.50 (12.7)	.85 (21.6)
			2	36	16.3									
			3	18	8.1									

INCHES  
(MM)

 ALL-STATES

BTID SERIES BEADED TIES  
CABLE TIES

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONAL TOLERANCES ARE:  
(X) +/- (XXX) +/-  
(XX) +/- ANGLES +/-

UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE GIVEN  
IN INCHES AND THIRD ANGLE  
PROJECTION.

DRAWN BY  
WJB  
DATE  
5-3-00  
CHK'D.

MATERIAL  
  
SEE CHART ABOVE

SCALE  
NONE  
DRAWING NO.  
10014-C  
DWG.  
A  
SIZE

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP
1	6-20-08	SB		REDRAWN AND DRAWING NO. WAS 10001-11				