



CATALOG NO.	TENSILE STRENGTH		MAX BUNDLE DIA.		A		B		C	
	lbs.	(kg)	in.	(mm)	in.	(mm)	in.	(mm)	in.	(mm)
RTSP-304	18	(8.160)	0.94	(24.0)	3.90	(100)	0.098	(2.5)	0.035	(0.9)
RTSP-308	18	(8.160)	2.00	(55.0)	7.85	(200)	0.098	(2.5)	0.035	(0.9)
RTSP-506	30	(13.600)	1.40	(36.0)	5.50	(140)	0.140	(3.5)	0.040	(1.0)
RTSP-508	30	(13.600)	2.00	(55.0)	7.85	(200)	0.140	(3.5)	0.040	(1.0)
RTSP-511	30	(13.600)	3.00	(80.0)	11.00	(280)	0.140	(3.5)	0.040	(1.0)
RTSP-608	50	(22.580)	2.00	(51.0)	7.30	(186)	0.180	(4.5)	0.045	(1.1)
RTSP-611	50	(22.650)	3.00	(76.0)	11.40	(290)	0.180	(4.5)	0.045	(1.1)
RTSP-614	50	(22.650)	4.00	(101.0)	14.10	(360)	0.180	(4.5)	0.045	(1.1)
RTSP-708	120	(54.400)	2.20	(56.0)	8.65	(220)	0.295	(7.5)	0.060	(1.5)
RTSP-714	120	(54.400)	4.40	(101.0)	14.10	(360)	0.295	(7.5)	0.060	(1.5)



ALL-STATES, INC.

1801 W. FOSTER AVE CHICAGO, IL 60640

SCALE:	MATERIAL: NYLON 6/6	DRAWN BY: SB
DATE:		APPRD BY: SB
TITLE:	RTSP-SERIES CABLE TIES	
FINISH:		
DEC. DIM. TOL ± 0.005	ALL DIMENSIONS IN INCHES	DRAWING NUMBER: 10016-C
FRACT. DIM. TOL ± 0.016		
ANGLE TOL ± 0.12		

R	RELEASE	6/19/2008	S.B.	S.B.
ISS.	ECN	DATE	BY	APP
REVISIONS				
USED ON				